

DFM 150

Medium Duty

DESIGN/CONSTRUCTION

- Designed to monitor two separate processes or gas flows
- Ideal for applications where shielding gas and back purge requirements are needed
- Designed to offer convenience for the maintenance and fabrication industries
- Brass body
- Teflon seat mechanism
- Sintered inlet filter – bronze
- Music wire – spring
- Piston – brass
- Cover tube – lexan

DIMENSIONS

5.5" W x 6.5" H x 5" D
(139.7 mm x 165.1 mm x 127.0 mm)

WEIGHT

2 lb. 9 oz. (1.16 kg)

PERFORMANCE

Maximum inlet – 3000 PSIG DFM 150
75 PSIG DFM 150S
Outlet pressure – 25 PSIG (preset)
Flow Capacity (See below)
Flow meter shows actual flow



Gas Service	Part No.	Model No.	Flow Range (SCFH)	CGA Inlet Connection	Max Inlet (PSIG)	HP Gauge	Replacement Flow Tube
Argon, Helium	0781-1153	DFM 150-580	5-50 (Argon) 20-150 (Helium)	580	3000	0-4000	1015-0057
CO ₂	0781-1206	DFM 150S	5-40 (CO ₂)	1/4" NPT (F)	75	0-100	1015-0057

Outlet Connection: 5/8"-18 RH(F), CGA 032
Preset Pressure: 25 PSIG