

# SR 310, SR 311, & SR 312

## Flow Meter

### DESIGN/CONSTRUCTION

- Designed for CO<sub>2</sub> application (non-siphoned tube cylinders)
- High flow CO<sub>2</sub> applications (SR 310 100 PSIG) (SR 311/312 100 SCFH) with adequate supply or source
- Designed for core wire applications
- Machined aluminum body & housing cap
- 2" (50.8 mm) gauge
- Stem type seat mechanism
- 1.75" (44.5 mm) diaphragm - fabric reinforced neoprene
- Self reseating relief valve (not designed to protect downstream equipment)
- Sintered inlet filter - bronze

### DIMENSIONS

8.38" W x 7.25" H x 2.5" D  
(212.9 mm x 184.2 mm x 63.5 mm)

### WEIGHT

2 lb. 15 oz. (1.33 kg)

### PERFORMANCE

Maximum inlet – 1500 PSIG

Delivery range – 100 SCFH

A regulator equipped with a flow gauge is not accurate when a back pressure in excess of 2 PSIG exists at the outlet. Back pressure is caused by a restriction in the equipment downstream of the flow gauge. Metering valves, kinked hoses or even very long hoses are restrictions that can cause back pressure. In applications where back pressure in excess of 2 PSIG can be expected, a regulator equipped with a flow meter should be used.

**WARNING:** High gas withdrawal rates may cause regulator freeze up and will require cylinder manifolding. Consult your gas supplier. See below for Gas Heater.

Gas Service	Part No.	Model No.	Flow Range (PSIG)	CGA Inlet Connection
CO <sub>2</sub>	0781-0355	SR 310 Adjustable Pressure Gauge	10-200 PSIG	320
	0781-0353	SR 311 (Preset @ 80 PSIG) Flow Meter	25-100 SCFH	320
	0781-0354	SR 312 Flow Gauge	0-100 SCFH	320

Outlet Connections: 5/8"-18 RH(F)  
Adapter: 5/8"-18(M) x 1/4" NPT(M)



SR 310



SR 311



SR 312